

La Premiere





Manufactured in France

1 temperature cabinet

Large size

Access Pack



Maturing cabinet, for wine ageing

Technical Specifications

Equipment
Standard shelf

Multifunctional shelf AEPHU1





Sliding 12 bottles

Storage





Sliding presentation 9 bottles

Fixed presentation 24 bottles

Equipment Optional shelves

(Mounted in the cabinet)







Storage shelf AXUH 77 bottles

Capacity 230 bottles maximum*

Temperature • Default setup temperature: 12°C / 54°F

·Temperature setting range from 6/43°F à 18°C/64°F

Design ⋅2

· 2 door options: glass with black frame or solid with black frame

·With or without handle**

·Stainless steel tube handle

·Central lock

·Black control panel

White interior lighting: 2 leds (ON/OFF)

· LED screen with touch-sensitive keys

·White screen display

Accessories

·4 multifunctional beechwood shelves

·1 EuroCave keyring

Optional: set of 20 black aluminium plates + 1 erasable felt-tip marker Ref : ID20-STYLO

Equipment

· Charcoal filter

·Clay ball humidity cassette

· 2 adjustable feet at the front

·Condensate drip tray at the back

Regulation

· Electronic regulation

Display of the real temperature inside the cabinet

· Hygrometry display

· Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)

· Automatic defrost

Technologies

Cold production:

Mixed air / Compressor R600a gas CE/US/UK/JA/AU/CH/C6

Cords:

Resistance

Heat production: Resis

Heat release: Automatic / Threshold: adjustable

Inner material: Aluminium

Exterior coating material:

Insulation type:

HPL panel (High pressure laminates)

Injected polyurethane foam (59mm)

^{*}Traditional Bordeaux format

^{**}Door with handle, not reversible



General features

| | Glass door | Solid door |
|------------------------------------|---------------------|---------------------|
| Empty wine cabinet net weight (kg) | 96 | 81 |
| Equipped cabinet net weight (kg) | 106 | 91 |
| Gross weight packaged (kg)* | 122 | 107 |
| Dimensions H x W x D (mm) | 1825 x 680 x 720*** | 1825 x 680 x 720*** |
| Dimensions packaged (mm) | 1950 x 720 x 760 | 1950 x 720 x 760 |
| Colour | Nero - RAL 9005 | Nero - RAL 9005 |

^{***}Incl. the separator at the back/ 690 mm without separator. The dimensions do not include the handle.

Energy efficiency & Consumption

| Cords | 230V-50Hz (R600a) | | 115V-60Hz (R600a) | |
|--|-------------------|-------------|-------------------|-------------|
| Type of door | Solid | Glass | Solid | Glass |
| Energy efficiency class | F | G | / | / |
| Annual energy consumption AEC (Kwh/year) | 132 | 190 | 172 | 212 |
| Sound emission (dB(A)) | 37 | 37 | 38 | 38 |
| Sound emission Class | С | С | / | / |
| Ambient operating temperature (°C/°F) | 0-35 / 32-95 | 0-30/ 32-86 | 0-35 / 32-95 | 0-30/ 32-86 |
| Volume utile (litres) | 461 | | | |

La Premiere, in a few words...

The fundamental by EuroCave.

The Première wine cabinet is designed for multiple uses. Concealed beneath its bold lines lies all the brand's expertise. Take your first steps into the world of EuroCave.







La Premiere





Manufactured in France

1 temperature cabinet

Large size

Premium Pack



Maturing cabinet, for wine ageing

Technical Specifications

Equipment Standard shelf

Multifunctional shelf AEPHU1





12 bottles





Sliding presentation 9 bottles

Fixed presentation 24 bottles

Optional shelves

(Mounted in the cabinet)







Storage shelf 77 bottles

Capacity 146 bottles maximum*

Temperature · Default setup temperature: 12°C / 54°F

·Temperature setting range from 6/43°F à 18°C/64°F

· 2 door options: glass with black frame or solid with black frame Design

·With or without handle**

·Stainless steel tube handle

·Central lock

·Black control panel

·White interior lighting: 2 leds (ON/OFF)

· LED screen with touch-sensitive keys

·White screen display

Accessories

·11 multifunctional beechwood shelves

1 EuroCave keyring

·Optional: set of 20 black aluminium plates + 1 erasable felt-tip marker Ref: ID20-STYLO

Equipment

·Charcoal filter

·Clay ball humidity cassette

· 2 adjustable feet at the front

·Condensate drip tray at the back

Regulation

· Electronic regulation

· Display of the real temperature inside the cabinet

· Hygrometry display

· Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)

· Automatic defrost

Technologies

Cold production:

Cords:

Mixed air / Compressor R600a gas

CE/US/UK/JA/AU/CH/C6

Heat production: Resistance

Heat release: Automatic / Threshold: adjustable

Inner material: Aluminium

Exterior coating material: HPL panel (High pressure laminates)

Insulation type: Injected polyurethane foam (59mm)

^{*}Traditional Bordeaux format

^{**}Door with handle, not reversible



General features

| Glass door | Solid door |
|---------------------|---|
| 96 | 81 |
| 125 | 110 |
| 141 | 126 |
| 1825 x 680 x 720*** | 1825 x 680 x 720*** |
| 1950 x 720 x 760 | 1950 x 720 x 760 |
| Nero - RAL 9005 | Nero - RAL 9005 |
| | 96 125 141 1825 x 680 x 720*** 1950 x 720 x 760 |

^{***}Incl. the separator at the back/ 690 mm without separator. The dimensions do not include the handle.

Energy efficiency & Consumption

| Cords | 230V-50Hz (R600a) | | 115V-60Hz (R600a) | |
|--|-------------------|-------------|-------------------|------------|
| Type of door | Solid | Glass | Solid | Glass |
| Energy efficiency class | F | G | / | / |
| Annual energy consumption AEC (Kwh/year) | 132 | 190 | 172 | 212 |
| Sound emission (dB(A)) | 37 | 37 | 38 | 38 |
| Sound emission Class | С | C | / | / |
| Ambient operating temperature (°C/°F) | 0-35 / 32-95 | 0-30/ 32-86 | 0-35 / 32-95 | 0-30/32-86 |
| Volume utile (litres) | 461 | | | |

La Premiere, in a few words...

The fundamental by EuroCave.

The Première wine cabinet is designed for multiple uses. Concealed beneath its bold lines lies all the brand's expertise. Take your first steps into the world of EuroCave.



